



### SUNFIND RPS 560 G3SQF3

Sunfind Solar Products developed our line of RPS Direct Water Pumping Systems (no batteries) to provide an efficient, cost effective solution for high lift and volume applications.

# Solar Array

The system comes with 4 Kyocera Solar 140W PV modules. Kyocera's advanced cell processing technology and automated production facilities produce a highly efficient multicrystal photovoltaic modules with a 20 year output warranty.

KD 140

Dimensions:

Weight 27.5 lbs

59.1" x 26.3" x 1.8"

Power (rated): 135W Peak Current 7.63A

Voltage: 12VDC Nominal



## **Top of Pole Mount:**

The System comes with a top of pole mount for 4 PV modules. The mount comes with all required hardware.

NOTE: The steel mounting pole is NOT included

# **Control System – CU 200 Advance Controller:**

The CU 200 controller allows the connection of the PV array to the pumping system.

# **Grundfos SQFlex Pump**

This industry leading pump is extremely versatile and reliable. The SQFlex is able to handle 30-300VDC and 90-240VAC.

This system is designed to have all four PV modules tied in series and feed the SQFlex directly. The pump will run when the sun is shining and shut down When there is not enough sun light available to run the pump.





#### What is included?

WORK ORDER / BILL OF MATERIALS	Units
Nominal 48VDC	
Kyocera 140W Blueish Module Class 1, Div. 2 CURRENTL: MOST AVAILABLE	4
Roll of Electrical Cable	16
1m Interconnect Piece	3
Hoffman Cabinet, 30" x 24" x 8"	1
Mounting Back Panel for Cabinet, 28" x 22"	1
3/4" Hole, 1/2" thread Strain Relief for PV Line and Battery Line	2
3/4" Hole, 1/2" thread Strain Relief for Float Switch	1
Marrettes to Tie solar Modules in Series	3
S-TPM3-KY135, Top of Pole Mount, 3 Kyocera 135-140 Modules	1
3/4" Hole, 1/2" For Solar Modules	7
600' @ 2 g/min 900W / 8.4A Max	1
Switch Box: On / Off. Used With Solar Direct System	1
Jordon MDI Mechanical Float Switch-Normally Closed	1
NMWU Cable: Wet locations and Direct Burial	186
	Nominal 48VDC  Kyocera 140W Blueish Module Class 1, Div. 2 CURRENTL: MOST AVAILABLE Roll of Electrical Cable 1m Interconnect Piece Hoffman Cabinet, 30" x 24" x 8" Mounting Back Panel for Cabinet, 28" x 22" 3/4" Hole, 1/2" thread Strain Relief for PV Line and Battery Line 3/4" Hole, 1/2" thread Strain Relief for Float Switch Marrettes to Tie solar Modules in Series S-TPM3-KY135, Top of Pole Mount, 3 Kyocera 135-140 Modules 3/4" Hole, 1/2" For Solar Modules  600' @ 2 g/min 900W / 8.4A Max Switch Box: On / Off. Used With Solar Direct System Jordon MDI Mechanical Float Switch-Normally Closed

### **Performance Calculations**

2.1 gpm @ 450'2.0 gpm @ 600'420W PV Array560W PV Array

For additional education material, product information and/or pricing, please contact a SUNFIND solar professional today.

Corporate Address:

SUNFIND SOLAR PRODUCTS 14, 7459 Edgar Industrial Bend Red Deer, AB T4P 3Z5 Monday-Thursday 7:30am - 4:00pm MST

Friday 7:30am-3:00pm MST

Location: Please stop by and visit us.

Tel: +1.403.343.6434 Fax: +1.403.343.6455

Email: info@sunfindsolarproducts.com Web: www.sunfindsolarproducts.com